



12" Sunlight Readable Display SL121

12" LED Sunlight Readable Monitor
WATERTIGHT – Built to stringent IP67 Standards
Screen – Anti-Glare, Rugged, Vandal Resistant
Extended Temperature Range
Outstanding Viewing Capabilities & Reliability
Easy to Install
Made in the U.S.A.



Specifications:

- **Panel Size: 10.3" X 13.7" X 3.3"**
- **Panel Color/Material: Gunmetal Gray Powder Coated Marine Grade Aluminum – welded seams**
- **Environment: Spray, UV, and Shock Resistant – Complies with NEMA 6/IP67 – (Strong Jet Spray) from any direction and temporary submersion**
- **Screen: Anti-glare, Rugged Vandal Resistant**
- **IP68 Rated (Submersible) Connectors provide 5000 reliable make/break connections – will clear 3/4" dia. hole for routing**
- **Mounting: Up to 100' From Your Computer**
- **Operating Temp: -30°C to +80°C**
- **Viewing Area: 12.1"**
- **Display Resolution: 1024(W)x768(H) XGA**
- **Viewing Angle: X-Axis -80° to 80° Y-Axis -80° to 80°**
- **Power: +12VDC Input**
- **Current Consumption: 1.9amps @ +12VDC**
- **Controls: Brightness Control for Sunlight to Nighttime Viewing**
- **Interface: Video Standard/Male DB15 Connector**
- **Options:**

Optical Bonding

Touch Screen: SL121TS

Ram Mount (Vibration damping rubber ball & socket)

Panel Mount or Flush Mounting

USB Video

Custom Cable Lengths' up to 100'

Special Features:

- **Optional Touch Screen**
- **Mounting: Pod, Ram Mount, Panel Mount**
- **Brightness: 1500NIT (Direct Sunlight Viewable)**
- **BNC Connector allows NTSC (DVD, TV & Camera)**
- **On Screen Menu for screen selection/adjustment**
- **Rugged, Waterproof Connectors**
- **2 Year Limited Warranty**



Sealed connectors, High Quality materials through and through

LCD Concepts, Inc.

2911 South Shore Blvd., Suite 125

League City, TX 77573

Phone: (281)334-5181

Fax: (866)580-8794

E-Mail: Sales@LCDConcepts.com

www.LCDConcepts.com

Thank you for using LCD Concepts, Inc. products